

Categories		IN-CEILING SPEAKER WITH BACKCAN					
Model Name		VC8	VC6			VC4	
DME library file name		VC8.cel	VC6.cel	VC6_sub.cel	VC4.cel	VC4_sub.cel	
Drive Mode		Passive	Passive	Passive	Passive	Passive	
Output Name		Full-range	Full-range	Full-range	Full-range	Full-range	
Gain	(dB)	0.0	0.0	0.0	0.0	0.0	
Delay	(ms)	none	none	none	none	none	
Polarity		Normal	Normal	Normal	Normal	Normal	
HPF	Freq (Hz)	40.0	40.0	100.0	40.0	100.0	
	Slope (dB)	12	12	24	12	24	
	Type	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth	
LPF	Freq (Hz)						
	Slope (dB)						
	Type						
PEQ1	Freq (Hz)	100.0	118.0	118.0	163.0	163.0	
	Level (dB)	6.5	6.5	3.5	4.0	4.0	
	Type	Bell	Bell	Bell	Bell	Bell	
	Q	5.3	5.3	2.8	2.8	2.8	
	Bandwidth	0.272	0.272	0.513	0.513	0.513	
PEQ2	Freq (Hz)	230	180	180	250	250	
	Level (dB)	-4.5	-3.5	-3.5	-6.0	-6.0	
	Type	Bell	Bell	Bell	Bell	Bell	
	Q	4.2	4.2	4.2	4.2	4.2	
	Bandwidth	0.343	0.343	0.343	0.343	0.343	
PEQ3	Freq (Hz)	1,180	250	250	1,900	1,900	
	Level (dB)	2.0	-6.0	-6.0	1.5	1.5	
	Type	Bell	Bell	Bell	Bell	Bell	
	Q	1.6	4.0	4.0	2.0	2.0	
	Bandwidth	0.888	0.360	0.360	0.714	0.714	
PEQ4	Freq (Hz)	4,100	2,500	2,500	6,000	6,000	
	Level (dB)	-1.0	2.0	2.0	-5.0	-5.0	
	Type	Bell	Bell	Bell	Bell	Bell	
	Q	2.4	2.5	2.5	3.0	3.0	
	Bandwidth	0.597	0.573	0.573	0.479	0.479	
PEQ5	Freq (Hz)	11,200	4,250	4,250			
	Level (dB)	-3.0	2.5	2.5			
	Type	Bell	Bell	Bell			
	Q	4.2	1.8	1.8			
	Bandwidth	0.343	0.792	0.792			
PEQ6	Freq (Hz)						
	Level (dB)						
	Type						
	Q						
	Bandwidth						
Limiter	Threshold						
	Attack						
	Release						